

The invention concerns the methods of preparing the packaging and can be used for sewing of multilayer cases for storage and transportation of diverse articles. A method of preparing the multilayer cases consists in that preliminary the units are cut out from basic material and lining, which are cut out of two parts, to one of which an excess material is added for forming of a protective flap. To the joints of the parts of lining of all components of article the fasteners are set, they are closed and then the basic material with lining is sewed on all components. Further the general shape of case is formed by connecting together all components, the fasteners in all components of article are opened and elastic gaskets are out into the openings. Then the fasteners are closed and covered with their protective flaps. At the end of sewing the case is turned out and it is ready to use. In the case, when it is necessary to produce the internal volume of case without interfering elements and components all fasteners and other elements are made on the facial material. For this, the basic material is composed of two parts, and lining is continuous and to the joints of each part of the basic material are put the fasteners, then they are closed. Further, the method is achieved according to above mentioned procedure, only after formation of finished case it is turned out, the fasteners are opened, and they are closed after mounting of their elastic gaskets. In this case, the elastic gaskets are made from the polymer, plastic, rubber, foam-rubber or their combination, and the fasteners on the case are used in the form of zippers or haberdashery buttons, or buttons or sticky fastener. This method allows to extend the use of multi-layer cases, increase their usability.